



Rewinder



HCR8002 Tuttet Change Logger

Application: 2 shafts auto exchange, suitable for rewinding various self-adhesive tapes.

Specification:

Machine Width:	1.0M/1.3M/1.6M	Max. Unwind O.D:	Ø800mm
Rewind Core I.D:	Ø3"	Max. Rewind O.D:	Ø300mm
Machine Speed:	180M / Min		

Feature:

1. Equipped with connected unwind base and web pulling out by jog motor control.
2. Equipped auto tension controller and surface type lay on roller on unwind base to make web wound out smoothly.
3. Driven by 2 A.C motors, 1 for web feeding, 1 for rewind tension control which automatically increasing torque on the rewind shaft when the finished roll O.D is getting bigger.
4. Center type winding with surface pressure roller to rewind various materials on different requests.

Optional Parts:

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Equipped with separated shaft type unwind base.
3. Tabbing Device :Automatic tabbing on the web during the production.
4. Slitting Device : Able to be equipped with air score knife and trim removable unit for trimming at both sides and wide size slitting.
5. The air for the rewind shafts will be automatically filled and leaked in the production.
6. material end cutting off and log roll wiping down are all applied automatically during the production and rewinding is finished.

(For reference only)



Hengcheng Machinery Co.,Ltd.

Manual and Automatic Single/Double Knife Roll Slitters and Slitter/Rewinders

E-mail:info@slitting-rewinder.com

URL:www.slitting-rewinder.com

Tel:+86-512-53100920

Fax:+86-512-53100720