



Slitter Rewinder



HCS3310 Duplex Center Slitter Rewinder

Application: 2 shafts center type winding, Suitable for slitting/rewinding various Papers, Soft films, label stocks.

Specification:

Machine Width:	1.0M/1.3M/1.6M	Max. Unwind O.D:	Ø1000mm
Rewind Core I.D:	Ø3"	Max. Rewind O.D:	Ø450mm
Min. Slitting Width:	30mm	Machine Speed:	200M / Min

Feature:

1. Equipped with separated shaft type unwind base, auto web guide and auto unwind tension controller.
2. Driven by connective 3 A.C motors, 1 for web feeding, 2 for rewind tension control which automatically increasing to que on the rewind shafts when the finished roll O.D is getting bigger.
3. Equipped different shafts to make tension on each roll the same even when the web thickness is not the same.
4. Finished rolls are unloaded by connected swing out type unloading stand, which is convenient on core unload.
5. Equipped with shear cutter, which is suitable for slitting various materials and trim unit is as strong blower.

Optional Parts:

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Shaftless Unwind Base : Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.
3. Connected Splice Table : Splicing materials smoothly in order to decrease production loss.

(For reference only)



Hengcheng Machinery Co.,Ltd.

Manual and Automatic Single/Double Knife Roll Slitters and Slitter/Rewinders

E-mail: info@slitting-rewinder.com

URL: www.slitting-rewinder.com

Tel: +86-512-53100920

Fax: +86-512-53100720