



Slitter Rewinder



HCSB Duplex Center Surface Slitter Rewinder

Application: 2 shafts center-surface type winding, Suitable for slitting/rewinding various Papers, Labels, Isolated paper/OPP/PET

Specification:

Machine Width:	1.0M/1.3M/1.6M	Max. Unwind O.D:	Ø800mm
Rewind Core I.D:	Ø3"	Max. Rewind O.D:	Ø500mm
Min. Slitting Width:	20mm	Machine Speed:	200M / Min

Feature:

1. Equipped with separated shaft type unwind base, auto web guide and auto unwind tension controller.
2. Driven by connective 3 A.C motors, 1 for web feeding, 2 for rewind tension control which automatically increasing to que on the rewind shafts when the finished roll O.D is getting bigger.
3. Horizontal control on rewind shaft arm is by air automatic adjustable, contacting pressure can be set on request.
4. Equipped with shear cutter, which is suitable for slitting various materials and trim unit is as strong blower.

Optional Parts:

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Shaftless Unwind Base : Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.
3. Connected Splice Table : Splicing materials smoothly in order to decrease production loss.

(For reference only)



Hengcheng Machinery Co.,Ltd.

Manual and Automatic Single/Double Knife Roll Slitters and Slitter/Rewinders

E-mail: info@slitting-rewinder.com

URL: www.slitting-rewinder.com

Tel: +86-512-53100920

Fax: +86-512-53100720